



OzoColor®

OzoColor® is a durable and decorative technological breakthrough in architectural maintenance coatings for interior wall finishes specifically formulated for high traffic public areas including hospitals, nursing homes, child care facilities, hotels, restaurants, retail stores and universities, as well as any other commercial areas. OzoColor® is not a paint but rather a combination of a roll on water based acrylic base (the color), and after drying, a water based urethane protective top coat, which is the key to our system as a protective and durable wall surface finish. It can be rolled or sprayed on like conventional paint. OzoColor® is environmentally safe and has been tested by independent labs to have on of the lowest levels of VOC's of any wall coating system.

ENVIRONMENTAL BENEFITS

- Certified laboratory testing confirms very low volatile organic compounds (VOCs)
- Is an environmentally safe product

SPECIFICATIONS

Product Name:	OzoColor®
Base Coat Composition:	Water-based acrylic
Protective Clear Coat:	Water-based urethane
Scrub Resistance:	ASTM-2486 11,735 cycles
Microbial Resistance:	ASMT-D3273 Mold, mildew, fungal and bacterial resistance @ 1 week incubation – 10 @ 2 week incubation – 10 @ 3 week incubation – 10 @ 4 week incubation – 10 * Material is microbial resistant as tested
Fire Resistance:	ASTM-84 Class A Flame
Washability:	Federal Standard- 141c, 61414 – Passes (no significant residual stain)
Hardness:	ASTM-D3363 Pass H
Stain Resistance:	ASTM-D1308 – Passes
Impact Resistance:	ASTM-D2794 – Passes 1/10" deformation
Flexibility:	ASTM-D522 – Passes 1/8"
Abrasion Resistance:	ASTM-4060 – CS-17 wheels @ 1,000 cycles 1,000 gr. – mg loss 64.9
Water Vapor Permeability:	ASTM-E96 –gr/100in ² /hr – Procedure B @ 5 mils – 101.6
VOC Content:	ASTM-D3960 – 44.4 gr/l (as manufactured with a percentage of water content)

TO MARKET®



A GREEN WORLD™

SPECIFICATIONS & ENVIRONMENTAL INFORMATION

OzoColor®

3844 N. W. 8th Street
Oklahoma City, OK 73107

1.866.772.4772
www.ToMkt.com

ADDITIONAL BENEFITS

- Made in the USA
- Easy installation
- A durable coating that is also decorative
- Low maintenance and long term good looks
- Out performs vinyl wall coverings, pain, and multi-color paints
- Provides unparalleled durability and visual appearance
- No seams to pop or corners to curl
- Designed to go over paint-ready dry wall surfaces
- Can be applied over pre-primed ceramic tile, concrete block, HardiBacker™ board, and laminates
- Resistance to:
 - Scuff marks
 - Hand and head oils
 - Abrasion
 - Mold and mildew