

TO MARKET®



A GREEN WORLD™



IMPORTANT!



PLEASE READ BEFORE INSTALLATION

This notice pertains to **ATMOSPHERE Recycled Rubber Flooring and Surfacing.**

1. Inspect your shipment for damage. Verify packing slip ensuring that the style, color, and quantity are correct.
2. Adhesives must not be exposed to freezing temperatures. Read technical data sheets and material safety data sheets for adhesive if applicable.
3. The products in front of you have gone through quality checks to ensure correct product, number of pieces, and that the physical properties, dimensions and visual appearance have passed our standards. However, for your own protection, we ask you to inspect this shipment for any apparent shortcomings before starting the installation by laying out ALL of the tiles for thorough visual inspection and complete acclimation (see also point 6 below). **Do not install product if there are any such shortcomings. To Market is not responsible for installation costs and will not be liable for material or labor if defective product is installed.**
4. Store material in a clean, dry, temperature controlled area. Recover with packaging provided after inspection has been complete to protect from dust and dirt prior to installation.
5. Referring to Atmosphere Rubber Tile flooring, install same side up as received.
DO NOT FLIP TILES DURING INSTALLATION!
6. Rubber expands and contracts with changes in temperature and humidity. Therefore, it is very important that all Atmosphere products be allowed to adjust to ambient temperature of the floor prior to starting installation. Acclimation time will depend upon storage time. See **SECTION I, MATERIALS, STORAGE & HANDLING, ITEMS D & E.** **Do not install** the tiles if they are not square and the appropriate thickness has not been reached.
7. It is important to keep a clean working surface at all times. Protect rubber flooring from construction dust and debris.
8. Keep ATMOSPHERE rubber flooring dry prior to and during installation.
9. **DO NOT USE TAPE** of any kind to help secure seams during glue down installation. Tape residue cannot be removed from the top surface.
10. **DO NOT GET ADHESIVE ON THE TOP SURFACE OF THE RUBBER FLOORING AS IT IS VIRTUALLY IMPOSSIBLE TO REMOVE. CONTACT YOUR DINO FLEX SUPPLIER IMMEDIATELY FOR SUGGESTED CLEANING METHODS IF THIS HAPPENS.**
TO MARKET will not be responsible for the replacement or cleaning of rubber tiles that have adhesive on the surface!

TO MARKET Installation & Maintenance Guidelines are enclosed in this shipment. Ensure you are familiar with all installation procedures prior to starting installation.

Toll Free: 1-866-772-4772
www.ToMkt.com