



SPECIFICATIONS & ENVIRONMENTAL INFORMATION

FORMIS®

3844 N. W. 8th Street
Oklahoma, City, OK 73107

TOTEM, SPIRIT, RAIN, HARVEST, GESSO, ETCHINGS, INDEX, PARADOX

1.866.772.4772
www.ToMkt.com

ENVIRONMENTAL BENEFITS

- Excellent indoor air quality, little or no VOC’s and non-allergenic
- Eliminates the need for a toxic seal coat or harmful particles, supporting a healthier air quality and indoor environment
- Can be totally recycled
- To Market accepts products at the end of their life to be reused and recycled in an effort to cut down on landfill waste and reduce the demand on natural resources.

SPECIFICATIONS

| | |
|---------------------------------------|---|
| Size/Thickness: | Harvest • Rain • Spirit • Totem • Gesso 18" x 18" - 1/8" (3mm - .120 gauge) |
| | Etchings • Index • Paradox 4" x 36" x 1/8" (3mm - .120 gauge) |
| Weight / Square Foot / Tile / Carton: | Harvest • Rain • Spirit • Totem • Gesso 2.31 lbs. / 2.25 square feet per tile, 36 square feet per carton |
| | Etchings • Index • Paradox 37 lbs. / 1.0 square feet per tile, 36 square feet per carton |
| Wear Layer: | 30 mil – Thermal Bonded |
| Finish: | Aluminum Oxide Porcelain Infused |
| Static Load Limit/ Static Electricity | ASTM-F-970 – 1,000 lbs/square inch Permanent Anti-Static |
| Critical Radiant Flux/Smoke: | ASTM-E-648 – Class I – 0.45 watts cm2 ASTM-E-662 – < 450 |

| | |
|-----------------------------|--|
| Stain/ Chemical Resistance: | ASTM-F-925 – No Change (5% acetic acid, rubbing alcohol, white mineral oil, 5% sodium hydroxide, 5% hydrochloric acid, 5% sulfuric acid, 5% household bleach, 5% household ammonia, olive oil, kerosene, 5% phenol disinfectant, unleaded gasoline) |
| Reference Specifications: | ASTM-F-1700 Class III, Type B-Embossed Surface (Meets or exceeds requirements for composition, size, thickness, squareness, flexibility, dimensional stability, and resistance to chemicals). |
| Slip Resistance: | Meets or Exceeds ADA requirements depending on surface texture (COF ASTM-D2047-93) |
| Warranty: | 10-Year Commercial Limited Warranty |

ADDITIONAL BENEFITS

- Fully integrated "aluminum oxide" porcelain infused finish, merged into the wear layer through a patented "thermal bonding" heat process.
- Superior wear, greater slip and scratch resistance, easier to clean.
- Formis™ surfaces improve coefficient of friction, requires **no wax, no stripping** of the floor at any time, and **no buffing**.
- Easily installed and shipped with its own brand of water-based adhesive.
- Will not promote microbial or fungal growth.