



METALLO, ETCHINGS, DAKOTA PLANK, GRANITE, CONCRETE AND INDEX

ENVIRONMENTAL BENEFITS

Ozoloc® features an environmentally friendly, adhesive free, patented and innovative connecting technology. Designed for high traffic areas in commercial or residential interiors, Ozoloc® can be installed directly over most old flooring with no floor prep as a floating and glue-less locking tile flooring system. Ozoloc® is a durable, flexible and performance driven solid surface flooring.

- No adhesives required.
- Covers minor surface irregularities on existing subfloors.
- 100% water resistant
- Fully integrated totally infused "ceramic bead barrier," merged into the wear layer through a patented "thermal bonding" process.
- Guaranteed not to chip or crack.
- Ozoloc® surfaces improve coefficient of friction, requires "no wax, no stripping, no buffing" of the floor at any time.
- Superior wear, greater slip resistance, easier to clean.
- Excellent indoor air quality, little or no VOC's, non-allergenic, will not promote microbial or fungal growth, and can be totally recycled.
- Does not require a toxic seal coat or harmful particles, supporting a healthier air quality and indoor environment.
- 10-Year Commercial Limited Warranty

SPECIFICATIONS

Style Name: Metallo • Etchings • Dakota Plank • Granite • Concrete • Index

Concrete • Size: Metallo – 18" x 36" Tiles
Etchings – 4" x 36" Planks
Dakota Plank – 6" x 48" Planks
Concrete • Granite • Index – 12" x 24" Tiles

Weight per Tile/Carton: Metallo – 8.3 lbs. per tile/50lbs. per carton
Etchings – 1.88 lbs. per plank/34 lbs. per carton
Dakota Plank – 3.7 lbs. per plank / 34 lbs. per carton
Concrete, Granite and Index – 3.77 lbs. per tile/34 lbs. per carton

Sq. Ft./Tile/Carton: Metallo – 4.5 sq. ft. per tile/6 tiles per carton/27 sq. ft. per carton
Etchings – 1 sq. ft. per plank/18 planks per carton/18 sq. ft. per carton
Dakota Plank – 2 s. ft. per plank/9 planks per carton/18 sq. ft. per carton
Concrete, Granite and Index – 2 sq. ft. per tile/9 tiles per carton/18 sq. ft. per carton

Gauge: 4.5mm

Wear Layer: 0.5mm (20 mil) – Thermal Bonded

Finish: Infused Ceramic Bead Barrier



METALLO, ETCHINGS, DAKOTA PLANK, GRANITE, CONCRETE AND INDEX

Seam/Installation System:	Ozoloc® Patented Locking System no adhesive required Pursuant to U.S. Patent No. 7,155,871 and 7,322,159
Coefficient of Friction:	ASTM-D2047-93 – 0.60
PSI Load:	ATM-F-970 – 1,000 lbs/square inch
Critical Radiant Flux/Smoke:	ASTM-E-648 – Class I – 0.45 watts cm2 ASTM-E-662 - <450
Stain/Chemical Resistance:	ASTM-F-925 – No Change (5% acetic acid, rubbing alcohol, white mineral oil, 5% sodium hydroxide, 5% hydrochloric acid, 5% sulfuric acid, 5% household bleach, 5% household ammonia, olive oil, kerosene, 5% phenol disinfectant, unleaded gasoline)
Reference Specifications:	ASTM-F-1700 Class III, Type B-Embossed Surface (Meets or exceeds requirements for composition, size, thickness, squareness, flexibility, dimensional stability, and resistance to chemicals.)
Slip Resistance:	Exceeds/Compliant with ADA Requirements – 100% Water Resistant
Warranty:	10-Year Limited Commercial Warranty
Maintenance:	Requires no wax, no stripping, no buffing, or toxic seal coat

Due to manufacturing tolerances, color and texture may vary slightly from samples shown. To view coordinates and for larger samples visit our website: www.ToMkt.com, or e-mail: samples@ToMkt.com or call customer service at (866) 772-4772.