

3844 N. W. 8th Street
 Oklahoma City, OK 73107

1.866.772.4772
 www.ToMkt.com

Unicork® has exceptional physical properties including acoustical and thermal insulation, durability, resistance to mold and mildew, naturally hypo-allergenic, and easy to clean. Unicork® is suitable for use in homes, offices, institutional, healthcare, and retail environments, including stores, restaurants, and any other commercial installation.

ENVIRONMENTAL BENEFITS

- Manufactured from the bark of cork trees, harvested by hand - no trees are destroyed in the manufacturing of this product
- Cork is a green, renewable and natural resource
- Natural thermal insulator
- Resistant to mold and mildew
- Naturally hypo-allergenic
- To Market accepts products at the end of their life to be reused and recycled in an effort to cut down on landfill waste and reduce the demand on natural resources.

LEED® INFORMATION

Materials and Resources (MR)- This product can contribute to attaining a point in the Materials and Resources credit for Rapidly Renewable Resources.

Environmental Quality (EQ)- This product can also contribute to points within the Environmental Quality section of the LEED Rating Systems as all accessories (adhesive, sealant, lacquer) meet the SCAQMD rule #1168, as required by LEED.

<i>LEED CREDIT</i>	<i>CATEGORY DESCRIPTIONS</i>	<i>QUALIFYING DESCRIPTION</i>	<i>PTS</i>
MR CREDIT 6 Material Resource	Rapidly Renewable resources	Cork qualifies as a rapidly renewable resource	1
EQ CREDIT 4.1 Environmental Quality	Low-Emitting Materials: Adhesives & Sealants	Low-VOC; complies with SCAQMD #1168	1
EQ CREDIT 4.3 Environmental Quality	Low-Emitting Materials: Composite Wood & Agrifiber Products	Product contains no added urea-formaldehyde	1

SPECIFICATIONS

- Product Name: Unicork® Flooring - BASIX
- Composition: Bark of cork trees, a renewable and natural resource
- Country of Manufacture: The Netherlands
- Size: 11.82" x 23.64" (30cm x 60cm)
- Thickness: 5mm



SPECIFICATIONS & ENVIRONMENTAL INFORMATION

To Market® | Unicork® Flooring

BASIX

Edge Configuration:	Straight edge all four sides.
Coefficient of Friction: Dry	ASTM-C1028-89, Exceeds ADA Requirements—.66
Critical Radiant Flux:	ASTM-E-648-97, Class II—.35 watts cm2 (NFPA 253/ FTM Standard 372)
Smoke Density:	ASTM-E-662-97, Passes—less than 450 (NFPA 258) Custom Colors, sizes and thickness are available. Please see your To Market sales representative for details.
Unicork™ Wall Base	Unicork® Wall Base is available in two sizes, in all Unicork® styles and colors.
Tall Wall Base	9.5cm high x 9mm thick x 117.475cm long Approximately 3.74" high x 3/8" thick x 46 7/8" long
Slim Wall Base	5.5cm high x 9mm thick x 117.475cm long Approximately 2.16" high x 3/8" thick x 46 7/8" long
Warranty:	Unicork® warrants its cork floor tiles to be free from manufacturer's defects. See Unicork® Installation, Maintenance & Warranty Guide for details.

ADDITIONAL BENEFITS

- Exceptional physical properties
- Acoustically superior
- Easy-to-clean
- Excellent resilience with inherent sound absorbing qualities due to the natural air filled structure of the cork core
- Cushioned feel under foot
- Suitable for use in homes, offices, institutional, healthcare, and retail environments, including stores, restaurants, and any other commercial installation.