



Pattern	Unicork 2
Composition	Bark of Cork Trees, a renewable and natural resource
Installation	Contact Cement
Size / Packaging	4.0 mm (floor): 23.63 x 11.82 (21.31 sq ft/pack) 5.0 mm (floor): 23.63 x 17.17 (5.81 sq ft/pack) 3.0 mm (wall): 23.63 x 11.82 (21.31 sq ft/pack)
Wall Base	Small = 2 x 1/8 high x 3/8 thick x 46 7/8 long Tall = 3 1/2 high x 3/8 thick x 46 7/8 long
Customization	19 stains colors available in 10 floor & 4 wall patterns
Edge	Square edge (<i>Beveled edge available for any pattern on 5mm</i>)
Finish	Available unfinished or unfinished with 3 coat lacquer (<i>2 applied at plant, product, and tools for 1 additional field application supplied</i>)
Certifications	FloorScore®; Mindful Materials
Warranty	10-Year Residential / 5-Year Commercial <i>See Unicork 2 Installation, Warranty and Maintenance Guide for details</i>
Dimensional Stability	ASTM F2199 – passes Length .0012 per 12" (.10%) Width: less than .015 per 12" (.13%) Initial Curl: less than .03 / Final Curl: less than .14
Smoke Density	ASTM E-662-97 – passes <450 (NFPA 258)
Load Limits	Specified Load 250 psi; Residual Compression <.005 Specified Load 300 psi; Residual Compression < .006 Indentation – ASTM F1914 – passes Caster Chair Test – ISO 4918 - passes
Slip Resistance	ASTM -C1028-89 Exceeds .64 dry / Exceeds .47 wet
Impact Sound Insulation (IIC)	EN 15102:2007 (A1:201) – passes ASTM E492, IIC - passes
LEED	Credit 6 – Rapidly Renewable Material – 1 pt Credit 4.1 – Low Emitting Material – 1 pt Credit 4.4 – Environmental Quality – 1 pt
Country of Manufacture	Netherlands

For additional information + product samples, please contact To Market Global.