

OZOG RIP GALLERY

PRODUCT SPECIFICATION



TO MARKET

Composition	Recycled Vinyl
Installation	Glue Down; Perimeter Glue
Size	Tate Collection Planks: 7.08" x 47.24" Orsay Collection Planks: 9.25" x 59.25"
Gauge	Tate Planks: 5.0mm and 4.0mm (new) Orsay Planks: 4.0mm (new)
Wear Layer	20 mil
Edge	Square: TM-401, TM-403, TM-404, TM-405, TM-409, TM-410 Bevel: TM-301, TM-303, TM-632, TM-633, TM-652, TM-655, TM-656, TM-657
Finish	Ozocoat+ Technology Advanced Ceramic Bead Barrier + Coating, Antifungal, Antibacterial, No Wax, No Buff
Certifications	FloorScore®; Environmental Product Declaration (EPD); ISO-9001 / ISO-14001
Warranty	Lifetime Residential / 15-Year Commercial
Reference Specifications	ASTM F-1700 Solid Vinyl Floor Tile – Class III, Type B-Embossed Meets & Exceeds Passing Requirements for composition, size, thickness, squareness, flexibility, dimensional stability and resistance to chemicals.
Radiant Panel	ASTM E-648 Critical Radiant Flux – Class I Meets & Exceeds Passing Requirements
Static Load Limit	ASTM-F-970 Meets & Exceeds Passing Requirements
Slip Resistance	ASTM D-2047 (James Machine) >.6 Meets & Exceeds Passing Requirements
Packaging	7.08" x 47.24" - 2.32 sq.ft./tile; 23.25 sq.ft./carton; 1,046 sq.ft./pallet; 45 cartons/pallet; 20 pallets/container 9.25" x 59.25" – 3.80 sq.ft./tile; 20 sq.ft./carton; 960 sq.ft./pallet; 48 cartons/pallet;20 pallets/container
Country of Manufacture	Korea and United States of America

For additional information + product samples, please contact To Market Global.