



Composition	Phthalate-Free Polyvinyl Chloride
Installation	Snap & Click
Underlayment	AcoustX Sound Absorbing Backing
Size	7.28" x 47.71"
Gauge	5.0mm = 4.0mm+1.0mm AcoustX backing
Wear Layer	20 mil
Edge	Bevel
Finish	Ozocoat+ Technology Advanced Ceramic Bead Barrier + Coating, Antifungal, Antibacterial, No Wax, No Buff
Certifications	FloorScore®; ISO-9001 / ISO-14001
Warranty	25-Year Residential / 10-Year Commercial
Reference Specifications	ASTM F-1700 Solid Vinyl Floor Tile – Class III, Type B-Embossed Meets & Exceeds Passing Requirements for composition, size, thickness, squareness, flexibility, dimensional stability and resistance to chemicals.
Radiant Panel	ASTM E-648 Critical Radiant Flux – Class I Meets & Exceeds Passing Requirements
Static Load Limit	ASTM-F-970 Meets & Exceeds Passing Requirements
Slip Resistance	ASTM D-2047 (James Machine) >.6 Meets & Exceeds Passing Requirements
Packaging	7.28" x 47.71" – 2.41 sq.ft./plank; 19.3 sq.ft./carton; 1,254 sq.ft./pallet; 65 cartons/pallet
Country of Manufacture	United States of America

For additional information + product samples, please contact To Market Global.