

# OZOGRIP ACOUSTX



TO MARKET

<b>Composition</b>	Recycled Vinyl
<b>Installation</b>	Glue Down; Perimeter Glue
<b>Underlayment</b>	AcoustX Sound Absorbing Backing
<b>Size</b>	Front Row: 9" x 36" Project: 19.68" x 39.37" Craze: 19.69" x 19.69" Moderne/Chic: 7.08" x 47.24"
<b>Gauge</b>	5.0mm = 4.0mm+1.0mm AcoustX backing
<b>Wear Layer</b>	20 mil
<b>Edge</b>	Square
<b>Finish</b>	Ozocoat+ Technology Advanced Ceramic Bead Barrier + Coating, Antifungal, Antibacterial, No Wax, No Buff
<b>Certifications</b>	FloorScore®; Environmental Product Declaration (EPD); ISO-9001 / ISO-14001
<b>Warranty</b>	Lifetime Residential / 15-Year Commercial
<b>Reference Specifications</b>	ASTM F-1700 Solid Vinyl Floor Tile – Class III, Type B-Embossed Meets & Exceeds Passing Requirements for composition, size, thickness, squareness, flexibility, dimensional stability and resistance to chemicals.
<b>Radiant Panel</b>	ASTM E-648 Critical Radiant Flux – Class I Meets & Exceeds Passing Requirements
<b>Static Load Limit</b>	ASTM-F-970 Meets & Exceeds Passing Requirements
<b>Slip Resistance</b>	ASTM D-2047 (James Machine) >.6 Meets & Exceeds Passing Requirements
<b>Acoustical</b>	IIC – 55 over 6" concrete slab

Packaging	7.08" x 47.24" - 2.32 sq.ft./tile; 23.25 sq.ft./carton; 1,046.25 sq.ft./pallet; 45 cartons/pallet; 20 pallets/container
	19.68" x 39.37" - 5.38 sq.ft./tile; 32.29 sq.ft./carton; 1,162.44 sq.ft./pallet; 36 cartons/pallet; 20 pallets/container
	19.69" x 19.69" - 2.69 sq.ft./tile; 26.91 sq.ft./carton; 1,184.04 sq.ft./pallet; 44 cartons/pallet; 20 pallets/container
	9" x 36" - 2.25 sq.ft./tile; 22.5 sq.ft./carton; 900 sq.ft./pallet; 40 cartons/pallet; 24 pallets/container
Country of Manufacture	Korea

For additional information + product samples, please contact To Market Global.