

# OZOGRIP WOVEN

## PRODUCT SPECIFICATION



TO MARKET

Composition	Virgin Vinyl – Phthalate Free
Installation	Glue Down; Perimeter Glue
Size	19.68" x 39.37"
Gauge	5.0mm
Wear Layer	20 mil
Edge	Square
Finish	Ozocoat+ Technology Advanced Ceramic Bead Barrier + Coating, Antifungal, Antibacterial, No Wax, No Buff
Certifications	FloorScore®; Environmental Product Declaration (EPD); ISO-9001 / ISO-14001
Warranty	Lifetime Residential / 10-Year Commercial
Reference Specifications	ASTM F-1700 Solid Vinyl Floor Tile – Class III, Type B-Embossed Meets & Exceeds Passing Requirements for composition, size, thickness, squareness, flexibility, dimensional stability and resistance to chemicals.
Radiant Panel	ASTM E-648 Critical Radiant Flux – Class I Meets & Exceeds Passing Requirements
Static Load Limit	ASTM-F-970 Meets & Exceeds Passing Requirements
Slip Resistance	ASTM D-2047 (James Machine) >.6 Meets & Exceeds Passing Requirements
Packaging	5.38 sq.ft./tile; 26.91 sq.ft./carton; 968.76 sq.ft./pallet; 36 cartons/pallet; 20 pallets/container
Country of Manufacture	Korea

For additional information + product samples, please contact To Market Global.