

OZOGRIP FAST TRACK



TO MARKET

PRODUCT SPECIFICATION

Composition	Virgin Vinyl – Phthalate Free
Installation	Glue Down; Perimeter Glue
Size	7.08" x 47.24" / 18" x 18" / 23.6" x 23.6"
Gauge	5.0mm
Wear Layer	20 mil
Edge	Bevel - 7.08" – Square - 18" and 23.6"
Finish	Ozocoat+ Technology Advanced Ceramic Bead Barrier + Coating, Antifungal, Antibacterial, No Wax, No Buff
Certifications	FloorScore®; Environmental Product Declaration (EPD); ISO-9001 / ISO-14001
Warranty	Lifetime Residential / 10-Year Commercial
Reference Specifications	ASTM F-1700 Solid Vinyl Floor Tile – Class III, Type B-Embossed Meets & Exceeds Passing Requirements for composition, size, thickness, squareness, flexibility, dimensional stability and resistance to chemicals.
Radiant Panel	ASTM E-648 Critical Radiant Flux – Class I Meets & Exceeds Passing Requirements
Static Load Limit	ASTM-F-970 Meets & Exceeds Passing Requirements
Slip Resistance	ASTM D-2047 (James Machine) >.6 Meets & Exceeds Passing Requirements
Packaging	7.08" x 47.24" - 2.32 sq.ft./tile; 23.25 sq.ft./carton; 1,046 sq.ft./pallet; 45 cartons/pallet; 20 pallets/container 18" x 18" - 2.25 sq.ft./tile; 22.5 sq.ft./carton; 1,012.5 sq.ft./pallet; 45 cartons/pallet; 20 pallets/container 23.6" x 23.6" - 3.87 sq.ft./tile; 23.25 sq.ft./carton; 930 sq.ft./pallet; 40 cartons/pallet; 26 pallets/container
Country of Manufacture	United States of America* *18"x18"/23.6"x23.6" - Korea

For additional information + product samples, please contact To Market Global.