

## PRODUCT SPECIFICATION



TO MARKET

Composition	Virgin Vinyl – Phthalate Free
Installation	Glue down
Available Sizes	7.25" x 48" / 6" x 36" / 4" x 36"
Gauge	2.0mm (0.080")
Available Wear Layers	6 mil and 8 mil
Finish	Advanced Ceramic Bead Barrier + Coating No Wax, No Buff
Certifications	FloorScore®; ISO-9001 / ISO-14001
Warranty	15-Year Residential / 7-Year Light Commercial
Reference Specifications	ASTM F-1700 Solid Vinyl Floor Tile – Class III, Type B-Embossed Meets & Exceeds Passing Requirements for composition, size, thickness, squareness, flexibility, dimensional stability and resistance to chemicals.
Radiant Panel	ASTM E-648 Critical Radiant Flux – Class I Meets & Exceeds Passing Requirements
Static Load Limit	ASTM-F-970 Meets & Exceeds Passing Requirements
Slip Resistance	ASTM D-2047 (James Machine) >.6 Meets & Exceeds Passing Requirements
Packaging	7.25" x 48" - 2.41 sq.ft./plank; 38.67 sq.ft./carton; 2,513.25 sq.ft./pallet; 65 cartons/pallet; 20 pallets/container  6" x 36" – 1.5 sq.ft./plank; 36 sq.ft./carton; 2,520 sq.ft./pallet; 70 cartons/pallet; 20 pallets/container  4" x 36" – 1 sq.ft./plank; 36 sq.ft./carton; 2,592 sq.ft./pallet; 72 cartons/pallet; 20 pallets/container
Country of Manufacture	China

For additional information + product samples, please contact To Market Global.