



DinoCoat

Low Maintenance Floor Treatment

Product Overview:

An exceptional durable copolymer treatment with limited gloss. Formulated to reduce the effects of “framing” or “shade variation” in recycled rubber flooring. Scrubs and recoats exceptionally well. Use on recycled rubber, vinyl, terrazzo, quarry tile, etc. (Not recommended for glazed store tiles.)

Features:

- Durable
- Easy to Apply
- Low Maintenance
- Slip Resistant

Benefits:

- Formulated to reduce the effects of “framing” or “shade variation” in recycled rubber flooring.
- Exceptionally resistant to scuffs and black heel marks.
- Leaves little or no concern for levelling and streaking problems.
- Recoats and blends well with existing coats.
- Stands up with excellent appearance with little maintenance required.
- Meets or exceeds CSMA and UL Standard ASTM D-2047-69 for slip resistance.

Applications and Dilutions:

Refer to product label for detailed application instructions. Use undiluted; covers 1200 – 1600 square feet per gallon.

Specifications:

- Physical Form – Thin Liquid
- Color – Opaque White
- Odor – Mild Acrylic
- pH (Concentrate) – 8.4 – 8.6
- Specific Gravity – 1.030
- Shelf Life – 1 Year Plus
- Flash Point – None
- WHMIS – Class D2B
- TDG – Not Regulated



710 S. Powerline Rd, Ste G
Deerfield Beach, FL 33442