

## PRODUCT SPECIFICATION



TO MARKET

Composition	Phthalate-Free Polyvinyl Chloride
Installation	Snap & Click
Underlayment	AcoustX Sound Absorbing Backing
Size	5.9" x 36.8" / 12" x 24"
Gauge	5.0mm = 4.0mm+1.0mm AcoustX backing
Wear Layer	20 mil
Edge	Bevel
Finish	Advanced Ceramic Bead Barrier + Coating, No Wax, No Buff
Certifications	FloorScore®; ISO-9001 / ISO-14001
Warranty	25-Year Residential / 10-Year Commercial
Reference Specifications	ASTM F-1700 Solid Vinyl Floor Tile – Class III, Type B-Embossed Meets & Exceeds Passing Requirements for composition, size, thickness, squareness, flexibility, dimensional stability and resistance to chemicals.
Radiant Panel	ASTM E-648 Critical Radiant Flux – Class I Meets & Exceeds Passing Requirements
Static Load Limit	ASTM-F-970 Meets & Exceeds Passing Requirements
Slip Resistance	ASTM D-2047 (James Machine) >.6 Meets & Exceeds Passing Requirements
Packaging	5.9" x 36.8" - 1.5 sq.ft./tile; 21 sq.ft./carton; 1,260 sq.ft./pallet; 60 cartons/pallet; 20 pallets/container  12" x 24" - 2 sq.ft./tile; 24 sq.ft./carton; 1,248 sq.ft./pallet; 52 cartons/pallet; 20 pallets/container
Country of Manufacture	China

For additional information + product samples, please contact To Market Global.